

HD NITEDEVIL EXT DOME 2.8-11MM & BRKT CAM325



HD Quality Wide Dynamic NiteDevil Dome Camera with Wall Bracket



Features

- ✓ 1080p @ 25FPS
- ✓ Excellent Picture Quality
- ✓ Privacy Masking
- ✓ IP66
- ✓ Low Light 0.02 Lux (Sens-up)
- ✓ Digital 64x Zoom
- ✓ Wide Dynamic Range
- ✓ Anti Vandal

Description

Our NEW NiteDevil HD Wide Dynamic Dome. Working in extremely low light conditions the NiteDevil produces exceptional results where other CCTV cameras wouldn't see a thing! With 1080p at 25fps this camera beats your standard analogue camera for high quality images.

For testing purposes there is a composite connection allowing you to connect a non HD test monitor when setting up the camera. It also has a RS485 connection for using the OSD.

Disclaimer

The technical specifications contained are given in good faith as being accurate but due to a continued program of improvement may change from time to time without notice. We apologise for any inconvenience due to changes of specification or errors and omissions within this document. Copyright

HD NITEDEVIL EXT DOME 2.8-11MM & BRKT CAM325



This model comes with a bracket for mounting on a wall.

The popular NiteDevil electronics were originally developed for bars and nightclubs, as the light sensitivity of the NiteDevil is so good that it can retain a colour picture in very low light conditions.

Wide Dynamic Range - The Dynamic Range of a camera is the difference between the darkest and brightest point of an image. In certain situations there will be a wide contrast between the two, such as a camera in a dimly lit pub or bar pointing towards a door or window on a brightly lit day. A camera with a WDR, is able to use shadowing detail on the dark areas as well as handle the brighter objects.

Disclaimer

The technical specifications contained are given in good faith as being accurate but due to a continued program of improvement may change from time to time without notice. We apologise for any inconvenience due to changes of specification or errors and omissions within this document. Copyright

HD NITEDEVIL EXT DOME 2.8-11MM & BRKT CAM325



Specifications

Image Sensor	1/3" 2.1M & 1.3 Megapixel COMS
Resolution	1080p 25fps/720p 50fps
Lens Type	2.8-11mm Vari-focal
Image Output	1 Volt Peak-Peak 75 ohm
Min. Illumination	0.02 Lux (sens up)
Input Voltage	12V DC/24V AC (Dual Voltage)
Current Consumption	150mA(12VDC) / 120mA(24VDC)
Dimensions	Dia 124mm, Base Dia 144mm
IP Rating	IP66
Signal to Noise Ratio	More than 50dB
Gain Control	Automatic
Video Connection	BNC Socket
Power Connection	Terminal Strip
Bracket	Supplied
Digital Zoom	64 x
Wide Dynamic Range	Yes
Sens Up	Yes

Disclaimer

The technical specifications contained are given in good faith as being accurate but due to a continued program of improvement may change from time to time without notice. We apologise for any inconvenience due to changes of specification or errors and omissions within this document. Copyright