

HD-SDI ALL-IN-ONE IR CAMERA WITH RS485 WHITE CAM380W

2.8-11
MM

VARI-F

1080p



RS485
OSD
CONTROL



A Broadcast Quality camera that's feature-packed in a sleek but tough external housing.



Features

- ✓ Superb HD Quality 1080p at 25fps
- ✓ Built-In IR LEDs
- ✓ 2.8 - 11mm Vari-focal Lens
- ✓ 62 x Digital Zoom PIP
- ✓ Die-Cast Case
- ✓ True Day Night electronics with WDR
- ✓ Extra SD Video Out for easy set-up
- ✓ Dual Voltage, 12V DC/24V AC
- ✓ True Wide Dynamic Range
- ✓ Cable managed bracket

Description

If you had any doubts over which model of HD camera to install then this is a winning choice! The CAM380 has all the low light surveillance benefits of NiteDevil technology and a Wide Dynamic Range with the added functionality of 40 IR LEDs.

This camera is a great choice for the installer who is looking for professional results in the shortest installation time possible thanks to its cable managed bracket, vari-focal lens with digital zoom function and a separate standard video output for easy set up and 'Up the Co-ax' control of the camera's OSD.

Additional features such as a choice of colours (white or grey) digital noise reduction, privacy masking and motion detection make this a truly versatile camera.

Disclaimer

The technical specifications contained are given in good faith as being accurate but due to a continued program of improvement may change from time to time without notice. We apologise for any inconvenience due to changes of specification or errors and omissions within this document. Copyright

HD-SDI ALL-IN-ONE IR CAMERA WITH RS485 WHITE CAM380W



Specifications

Image Sensor	1/3" 2.1M Panasonic Megapixel CMOS
Resolution	1080p 25fps/780p 50fps (PAL)
Lens Type	2.8-11mm Vari-focal
Image Output	HD-SDI / 1V P-P 75 ohm
Min. Illumination	0 Lux with LEDs on
Day/Night Function	True Day Night
InfraRed LEDs	40
Input Voltage	12/24V Dual Voltage
Current Consumption	170mA IR Off / 300mA IR On
Dimensions	78mm Dia x 140mm (Ex Sunshield & Bracket)
IP Rating	IP66
Signal to Noise Ratio	More Than 50dB
Gain Control	Automatic
Video Connection	BNC Socket
Protocol	PELCO D
Bracket	Supplied
Finish	White
Build	Die-Cast Aluminium
Backlight Compensation	Selectable
Operating Temperature	-10 to 50 deg C
White Balance	Selectable
Digital Zoom	62 x Picture In Picture
Wide Dynamic Range	Yes
Sens Up	x30

Disclaimer

The technical specifications contained are given in good faith as being accurate but due to a continued program of improvement may change from time to time without notice. We apologise for any inconvenience due to changes of specification or errors and omissions within this document. Copyright